

G71L - LATCHING

Make Only Load Switching
RoHS Compliant

70 kV



FEATURES

- Latching coils for low power consumption and to ensure relay will remain in last position, even when no voltage is applied to the coil

G71LA

- Sealed 70 kV isolation in about 6.3 cubic inch (100 cubic cm) package - your will be system the smallest in the industry!
- SF-6 gas filled for capacitive discharge with no x-ray emissions
- Pre-tinned, optional length, high voltage leads making installation easy fast and easy
- Great for charging & discharging capacitors with no bounce under load
- GIGAVAC exclusive replaceable coils

G71LC

- Same great features as the G71A and G71B
- Double Throw (SPDT) for polarity reversal and multiple power source switching

PRODUCT SPECIFICATIONS

Contact & Relay Ratings	Units	G71LA	G71LC
Contact Form		A	C
Contact Arrangement		SPST	SPDT
Voltage, Test Max., Contacts & to Base (15 μ A Leakage Max, dc or 60Hz)	kV Peak	75	75
Voltage, Operating Max., Contacts & to Base (15 μ A Leakage Max.)			
dc	kV Peak	70	70
60 Hz RMS	kV Peak	30	30
2.5 MHz	kV Peak	-	-
16 MHz	kV Peak	-	-
32 MHz	kV Peak	-	-
Current, Continuous Carry Max			
dc or 60 Hz	Amps	10	10
2.5 MHz	Amps	-	-
16 MHz	Amps	-	-
32 MHz	Amps	-	-
Coil Hi-Pot (V RMS, 60 Hz)	V	500	500
Capacitance			
Across Open Contacts	pF	-	-
Contacts to Ground	pF	-	-
Resistance, Contact Max @ 1A, 28 Vdc	ohms	2.0*	2.0*
Operate Time	ms	20	20
Reset Time	ms	15	15
Life, Mechanical	cycles	.5 million	.5 million
Weight, Nominal	g (oz)	336 (12)	336 (12)
Vibration, Operating, Sine (55-500 Hz Peak)	G's	10	10
Shock, Operating, 1/2 Sine 11ms (Peak)	G's	20	20
Temperature Ambient Operating	°C	-50 to +85	-50 to +85

COIL RATINGS

Nominal, Volts dc	26.5
Pick-up, Volts dc, Max.	22
Reset, Volts dc	1 - 10
Coil Resistance (Ohms $\pm 10\%$)	-

Ratings listed are for 25°C, sea level conditions.
Coils are polarity sensitive.
Observe polarity marked on coil terminals.

For more information, refer to

Relay User Instructions

G71 L A 8 4 1

Latching Designator

Contact Form

A = SPST
C = SPDT

Coil Voltage **

8 = 26.5 Vdc, Turret Terminal

High Voltage Connections

4 = Flying Leads, 12"
7 = Flying Leads, 72"
8 = Flying Leads, 36"

Mounting

1 = Threaded

* Contact resistance for gas-filled measured at 28 Vdc, 1 Amp

** Order the relay with the part number as shown. The latching "L" designator and the coil voltage will not appear in the P/N on the relay but will be indicated on the label that is on the base of the relay. Observe coil polarity.