


Data-Sheet-Variable Vacuum Capacitor



CKTBS300/15/150



Specification	
Capacity $C_{\max}$ (nominal)	300pF
Capacity $C_{\min}$ (nominal)	30pF
Voltage (Peak Test U_{pt} /Peak Working U_{pw})	15KVp/9KVp
Capacity Tolerance (Linear Range)	10%
Max. Current $I_{\max}$ at 13.56MHz with	150Arms
Water Cooling	1 L/min
Capacitance per turn	20.5pF/turn
Turns	14.5 ± 1
Torque	$\leq 0.2 \text{ N} \cdot \text{m}$
Net Weight	1.6kg



$I_{\max}$ for 1L/min water cooling; max. water temp. at inlet: 70°C



UNLESS OTHERWISE SPECIFIED:

≤ 30 : ± 0.5 30~400: ± 1.2 ≥ 400 : ± 2.5 $\angle$: $\pm 1^\circ$

Address: ST28 Xihu Road, Kunshan, Jiangsu Province, China
TEL: +86 (512) 36872110

Rev: 10

Web: www.glvac.com
FAX: +86 (512) 36872122

Page 1/1

Issue: 17-Oct-2024

E-mail: e-sales@glvac.cn
Zip Code: 215333